

**IN THE CLAIMS:**

1. (PREVIOUSLY PRESENTED) A method for controlling a hand-off of an MS (Mobile Station) for home zone service in a mobile telecommunications system, comprising the steps of:

(a) establishing a call connection between said MS and a BTS (Base Transceiver Station) providing the home zone service, wherein a home zone pertaining to the home zone service is defined by a fixed network in which the MS is further registered for use;

(b) requesting a BSC (Base Station Controller) to make the hand-off to a hand-off targeted BTS via said BTS;

(c)(i) causing said BSC to receive a home zone information of said MS from an MSC (Mobile Switching Center) wherein the home zone information pertains to said home zone and includes a home zone list and a subscriber class of said MS;

(c) (ii) causing said BSC to determine whether the hand-off targeted BTS belongs to the home zone using the home zone list;

(d) (i) performing the hand-off of said MS to said hand-off targeted BTS if said hand-off targeted BTS belongs to the home zone;

(d)(ii)determining whether said MS is registered to be used only in the home zone or not by retrieving the subscriber class when said hand-off targeted BTS does not belong to the home zone;

(e) dropping said call connection if said hand-off targeted BTS does not

belong to the home zone and if said MS is registered to be used only in the home zone service; and,

(f) performing the hand-off of said MS to said hand-off targeted BTS if said hand-off targeted BTS does not belong to the home zone and said MS is registered to be used both in the home zone service and a non-home zone service.

2. (PREVIOUSLY PRESENTED) The method as defined in Claim 1, wherein the step (a) of establishing said call connection further includes the steps of:

(g) causing said BSC to request the home zone information of said MS from a MSC (Mobile Switching Center) in response to a request to establish said call connection between said MS and said BTS;

(h) causing said MSC to send the home zone information to said BSC; and,

(i) storing the home zone information in said BSC.

3. (PREVIOUSLY PRESENTED) The method as defined in Claim 2, wherein the home zone information includes a home zone list having a plurality of BTSs providing the home zone service to said MS and a subscriber class information specifying whether said MS is registered to be used in the non-home zone service.

4. (PREVIOUSLY PRESENTED) The method as defined in Claim 2,

wherein the step (h) of sending the home zone information from said MSC to said BSC is achieved through a call proceeding message.

5. (ORIGINAL) The method as defined in Claim 2, wherein the home zone information is stored in a database.

6. (ORIGINAL) The method as defined in Claim 5, wherein the database is stored in an LRS (Location Registration System).

7. (CANCELLED).

8. (CANCELLED).

9. (PREVIOUSLY PRESENTED) The method as defined in Claim 1, wherein the step (e) of dropping said call connection further includes the steps of sending a BTS acknowledging signal to said MS, sending a warning message to said MS, and causing said MS to output said warning message to inform the subscriber of said MS.

10. (PREVIOUSLY PRESENTED) The method as defined in Claim 9, wherein said warning message comprises either one of visual characters, tones, and flash light.

11. (CANCELLED).

12. (CANCELLED).

13. (CANCELLED).

14. (CANCELLED).

15. (CANCELLED).

16. (CANCELLED).